

PRODUCT DATA SHEET**LUBEMORE ULTRA 10W****DESCRIPTION**

LUBEMORE ULTRA 10W is heavy duty engine oil and is blended from highly refined, high viscosity index base stocks and contain appropriate dosages of detergent-dispersant and antioxidant additives to meet the stated performance standards.

APPLICATIONS

LUBEMORE ULTRA 10W is recommended for all classes of supercharged diesel engines of high speed high output such as those in heavy duty diesel vehicles & Tractors, Earth moving & off-highway equipment, Transmission systems of caterpillar equipment, large generator sets. Also specially used in earth moving equipment where same oil is used for engine & hydraulic system.

KEY FEATURES

- Effectively combat against high sulphur fuels.
- Excellent engine cleanliness & minimizes deposit and wear.
- Excellent control of cold sludge and corrosive wear.
- Possess excellent oxidation stability ensuring long service life especially in transmission systems.

PERFORMANCE STANDARD MEETS:

- API- CD
- E-DL 2 of IS : 1365
- US MIL-L-45199B
- Caterpillar Series 3
- Hydraulic fluid type C2 specification of Detroit Diesel Allison

SPECIFICATION

Tests	Test Method	Specification	Typical value
Kinematic Viscosity @ 100 deg c, cSt	ASTM D-445	5.5 - 6.5	6.2
Viscosity Index, Min.	ASTM D-2270	100	105
Flash Point, (COC), deg C, Min.	ASTM D-92	190	195
Pour Point, deg C, Min.	ASTM D-97	-27	-27
TBN,mg KOH/g.	ASTM D-2896	9.5 - 11.5	11

* Due to continual product research and development, the information contained herein is subject to change without notice.